

Declaration of performance

Nr. 001 - Feinsteinzeug

1. **Product type for identification:** Ceramic tiles, dry pressed with a water absorption $\leq 0,5$ % (group BIa)
2. **Intended use:** Wall and floor tiles; indoor and outdoor
3. **Manufacturer:** Panariagroup Deutschland GmbH,
Kerastraße 1,04703 Leisnig
4. **System for assessing and inspecting the performance reliability of the construction:** System 4
5. **Harmonised standards:** EN 14411:2016
6. **Declared performance:**

Essential properties	Performance
Fire behaviour	A1fl/A1
Emission of hazardous substances:	
- cadmium	NPD
- lead	NPD
- other	NPD
Breaking load	≥ 1300 N
Bending strength	≥ 35 N/mm ²
Slip resistant properties	NPD
Tactility	NPD
Bond strength / adhesion:	
- cement-based mortar, type C1	$\geq 0,5$ N/mm ²
- cement-based mortar, type C2	$\geq 1,0$ N/mm ²
Durability in the case of:	
- uses in internal spaces	Passed
- uses in external spaces: freeze-thaw cycle resistance	Passed

7. **The performance of the product as stated in section 1 corresponds to the declared performance in accordance with number 6. The manufacturer named in section 3 is solely responsible for the preparation of this declaration of performance.**

Signed for and on behalf of the manufacturer by: Peter Wilson, Geschäftsführer

Leisnig, 02.04.2025

